




## UV Sensor Probe

Model: AP-UVx-1y

### General features:

- Compact package with sapphire window
- Single power supply
- Analog 0-5 V or 4-20 mA output
- High sensitivity and proved reliability



**Applications:** Radiant intensity measurement for UV curing, UV sterilization monitoring

### Specifications:

General parameters				
Dimensions	Window diameter (mm)	Weight (g)	Case material	
See drawing below	6	36	Al	
Parameters	Symbol	Value	Unit	Remark
Maximum ratings				
Operation temperature	$T_{op}$	-20-85	°C	
Storage temperature	$T_{sp}$	-30-95	°C	
Electro-optical characteristics (25 °C)				
Supply voltage	$V_{cc}$	7-24	V	DC
Output signal	$I_{out}$	4-20	mA	2 wire circuit (AP-UVx-11)
				3 wire circuit (AP-UVx-12)
	$V_{out}$	0-5	V	3 wire circuit (AP-UVx-13)
Detection wavelength range <sup>1</sup>		220-290	nm	AP-UVC-1y
		220-325		AP-UVB-1y
		220-370		AP-UVA-1y
		290-440		AP-UVV-1y
UV power intensity measurement range	P	0-200	mW/cm <sup>2</sup>	See other options <sup>2</sup>
Connection				
Cable length <sup>3</sup>	2 m			

<sup>1</sup> UVA, UVB, UVC, UVV and full UV band are all available upon request.

<sup>2</sup> UV power intensity measurement range: 0-200 mW/cm<sup>2</sup> (standard), 0-1 W/cm<sup>2</sup> (option).

<sup>3</sup> Cable length can be customized upon request.



# UV Sensor Probe

Model: AP-UVx-1y

Drawing:

